



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

TARPCOTE CLEAR PVC 2000

DESCRIPTION

TARPCOTE CLEAR PVC 2000 is a tough and durable high performance waterborne coating specifically formulated for application to flexible PVC by rollercoater. It is suitable for outdoor use.

FEATURES

- Excellent foaming
- Good outdoor durability
- Good resistance to scuff and abrasion
- Excellent flexibility - will not whiten on creasing or folding
- Non-blocking - will not stick in the reel
- Excellent adhesion to flexible PVC
- Medium gloss finish

PROPERTIES

- | | |
|---------------------------|-----------------------------------|
| ▪ Gloss | 50 – 55% @ 60° |
| ▪ Solids Content | 31.8 ± 1% |
| ▪ Package Viscosity | 22 – 25 Sec DIN Cup No. 4 @ 25°C. |
| ▪ Recommended Film Weight | 3 – 4 g/m ² (dry) |
| ▪ Reducer | Water |
| ▪ Retarder | Butyl Oxitol® (2-Butoxy Ethanol) |
| ▪ Wash Up | Aquawash WBC675 |
| ▪ Flash Point | Not flammable |

DRYING

By means of hot air current or infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

THIS DATA SUPERCEDES ANY DATA ISSUED PRIOR TO APRIL, 2020

