



60 Carlisle Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

AQUA COAT MATT WBM369

DESCRIPTION

AQUA COAT MATT WBM369 is a general-line in-line waterbased coating formulated to produce a smooth matt finish. The dry film is resistant to polishing and candling.

FEATURES

- Matt finish
- Does not streak
- Exceptional press stability
- Excellent anti-blocking characteristics
- Excellent scuff/rub resistance
- Ease of application
- Smooth finish

PROPERTIES

- | | |
|---------------------------|----------------------------------|
| ▪ Solids Content | 24.7 ± 1.0% |
| ▪ Package Viscosity | 25 – 27 Sec DIN Cup No.4 @ 25°C |
| ▪ Gloss (60°) | 5 – 10% (on art paper) |
| ▪ pH | 8.6 – 8.9 |
| ▪ Recommended Film Weight | 4 – 6 g/m ² (wet) |
| ▪ Reducer | water |
| ▪ Wash Up | water, water/alcohol or AQUAWASH |
| ▪ Flash Point | non-flammable |

DRYING

By means of infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

GENERAL

The components used in AQUA COAT MATT WBM369 would be compliant with FDA regulations for indirect food contact.

THIS DATA SUPERCEDES ANY DATA ISSUED PRIOR TO NOVEMBER 2020

