



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

AQUASEAL WBS111

DESCRIPTION

AQUASEAL WBS111 is a waterbased sealer coating designed for rollercoater application to paper and carton board.

FEATURES

- Fast drying
- Excellent scuff resistance
- Good holdout and flow out characteristics
- Excellent flexibility (non-cracking properties over wet ink)
- Excellent sealing properties
- Excellent defoaming

PROPERTIES

▪ Solids Content	32.6 ± 1.0%
▪ Package Viscosity	24 – 25 Sec DIN Cup No.4 @ 25°C
▪ Gloss (60°)	70 – 75%
▪ pH	8.2 – 8.8
▪ Wash Up	water, water/alcohol or AQUAWASH
▪ Flash Point	non-flammable
▪ Recommended Film Weight	4 – 6 g/m ² (wet)

DRYING

By means of infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened drums at 20°C.

GENERAL

In their dry state, the components used in AQUASEAL WBS111 would be compliant with FDA regulations for direct food contact.

THIS DATA SUPERCEDES ANY DATA ISSUED PRIOR TO NOVEMBER, 2020

