



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

AQUAGLOSS WBS117

DESCRIPTION

AQUAGLOSS WBS117 is a quick drying, general-purpose, gloss, waterbased coating for paper and board. Aquagloss is a coating with excellent ANTI-BLOCKING AND RELEASE CHARACTERISTICS.

FEATURES

- Rapid drying
- Excellent release
- Excellent press stability
- Good scuff resistance
- Excellent gloss

PROPERTIES

- | | |
|---------------------------|----------------------------------|
| ▪ Gloss (60°) | 65 – 70% (Valkraft board) |
| ▪ Solids Content | 31.6 ± 1.0% |
| ▪ Package Viscosity | 30 – 31 Sec DIN Cup No.4 @ 25° C |
| ▪ pH | 8.5 – 8.9 |
| ▪ Recommended Film Weight | 4 – 6 g/m ² (wet) |
| ▪ Reducer | water |
| ▪ Wash Up | water, water/alcohol or AQUAWASH |
| ▪ Flash Point | non-flammable |

DRYING

By means of infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20° C.

GENERAL

AQUAGLOSS WBS117 has been formulated using EU Regulatory Guidelines for the safe use in Food Packaging. In addition, the product is compliant with the Nestlé Guidance Note on Packaging Inks – version 02-2014 and Woolworths Packaging Guidelines.

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR TO NOVEMBER, 2020

