



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

AQUA FAST FOOD GLOSS WBS127

DESCRIPTION

AQUA FAST FOOD GLOSS WBS127 is a heat resistant, waterbased coating formulated for use on low odour, low migration food packaging. It is suitable for in-line wet on wet application over lithographic inks, producing a smooth gloss finish. It is especially suited for double-sided jobs where blocking is a problem.

FEATURES

- Low odour
- Heat resistant
- Low migration
- Exceptional press stability
- Excellent anti-blocking characteristics
- Excellent scuff/rub resistance
- Smooth, gloss finish
- Ease of application
- Does not streak

PROPERTIES

- | | |
|---------------------------|----------------------------------|
| ▪ Solids Content | 37.0 ± 1.0% |
| ▪ Package Viscosity | 50 – 54 Sec DIN Cup No.4 @ 25°C |
| ▪ Gloss (60°) | 55 – 60% (Valkraft board) |
| ▪ pH | 8.2 – 8.8 |
| ▪ Recommended Film Weight | 4 – 6 g/m ² (wet) |
| ▪ Reducer | water |
| ▪ Wash Up | water, water/alcohol or AQUAWASH |
| ▪ Flash Point | non-flammable |

DRYING

By means of infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

GENERAL

The components used in AQUA FAST FOOD GLOSS WBS127 would be compliant with FDA regulations for indirect food contact.

THIS DATA SUPERCEDES ANY DATA ISSUED PRIOR TO NOVEMBER, 2020

