



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

AQUA DOUBLE-SIDED GLOSS WBS357

DESCRIPTION

WBS357 has been specifically formulated to meet the requirements for double sided coating. Aqua double-sided gloss is quick drying, with excellent ANTI-BLOCKING AND RELEASE CHARACTERISTICS.

FEATURES

- Rapid drying
- Excellent release
- Excellent press stability
- Good scuff resistance
- Excellent gloss

PROPERTIES

- | | |
|---------------------------|----------------------------------|
| ▪ Gloss (60°) | 70 – 80% |
| ▪ Solids Content | 32.0 ± 1.0% |
| ▪ Package Viscosity | 40 – 42 Sec DIN Cup No.4 @ 25°C. |
| ▪ pH | 8.2 – 8.5 |
| ▪ Recommended Film Weight | 4 – 6 g/m ² (wet) |
| ▪ Reducer | water |
| ▪ Wash Up | water, water/alcohol or AQUAWASH |
| ▪ Flash Point | non-flammable |

DRYING

By means of infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR TO NOVEMBER, 2020

