



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

AQUA POLYGLOSS WBS527

DESCRIPTION

WBS527 AQUA POLYGLOSS has been specifically formulated to give a high gloss, smooth finish over wet conventional lithographic inks. Aqua Polygloss is quick drying, with excellent scuff and abrasion resistance for BIB carton work.

FEATURES

- Rapid drying
- Excellent gloss
- Excellent scuff
- Excellent abrasion resistance
- Flexible and resilient coating

PROPERTIES

▪ Gloss (60°)	70 – 80%
▪ Solids Content	39.8 ± 1.0%
▪ Package Viscosity	50 Sec DIN Cup No.4 @ 25°C.
▪ pH	8.2 – 8.5
▪ Recommended Film Weight	4 – 6 g/m ² (wet)
▪ Reducer	water
▪ Wash Up	water, water/alcohol or AQUAWASH
▪ Flash Point	non-flammable

DRYING

By means of infra-red drying unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, un-opened containers at 20°C.

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR TO DECEMBER, 2020

