



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

UV ROLLERCOAT VARNISH UVR10

DESCRIPTION

UV ROLLERCOAT VARNISH UVR10 is a gloss UV overprint varnish for paper and board designed to provide a high gloss and yield finish for food & label packaging. UVR10 is suitable for roller coating application in-line on wet UV inks or off-line on dry conventional inks.

FEATURES

- High slip
- Low foaming
- Outstanding mileage
- Acceptable odour level
- Good adhesion to a variety of substrates
- High scuff and abrasion resistance
- Acceptable odour level
- Excellent gloss
- Fast curing

PROPERTIES

- | | |
|----------------------------|-----------------------------------|
| ▪ Cure Speed (80W) | 65 m/min |
| ▪ Relative Density at 25°C | 1.015 |
| ▪ Viscosity | 14 – 16 Sec Zahn Cup No.4 at 25°C |
| ▪ Solids Content | 100% |
| ▪ Recommended Film Weight | 3 – 5 g/m ² |
| ▪ Gloss at 60° | 90 – 93% (Valkraft board) |
| ▪ Angle of Slide | < 20° |
| ▪ Foaming Test | < 20% |
| ▪ Flashpoint | N/A |

DRYING

By means of UV curing unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

GENERAL

The components used in UV ROLLERCOAT VARNISH UVR10 would be compliant with FDA regulations for indirect food contact.

UVR10 does not contain ITX (Isopropylthioxanthone) , TAA (Titanium Acetylacetonate).

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR TO FEBRUARY, 2020

