



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

UV DULL MATT VARNISH UVRM41

DESCRIPTION

UV DULL MATT VARNISH UVRM41 is a matt UV overprint varnish for paper and board designed to provide a low odour and dull matt finish for food & label packaging. UVRM41 is suitable for roller coating application in-line on wet UV inks or off-line on dry conventional inks.

FEATURES

- Low odour
- Dull matt finish
- High scuff and abrasion resistance
- Good adhesion to a variety of substrates
- Good sealing properties
- Excellent slip
- Low foaming

PROPERTIES

- | | |
|---------------------------|------------------------------------|
| ▪ Cure Speed (80W) | 40 m/min |
| ▪ Relative Density @ 25°C | 1.17 |
| ▪ Viscosity | 16 – 17 Sec. Zahn Cup No. 4 @ 25°C |
| ▪ Solids Content | 100% |
| ▪ Recommended Film Weight | 3 – 5 g/m ² |
| ▪ Gloss @ 60°C | < 15% on Vulkraft Board |
| ▪ Flashpoint | N/A |

DRYING

By means of UV curing unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

GENERAL

The components used in UV Dull Matt Varnish UVRM41 would be compliant with FDA regulations for indirect food contact.

UVRM41 does not contain ITX (Isopropylthioxanthone) , TAA (Titanium Acetylacetonate).

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR TO APRIL, 2020

