



13 Natal Street, Paarden Eiland, 7405
P.O. Box 498, Paarden Eiland, 7420
National: 0861 105 973
CPT: 021 510 5811
Fax: 021 510 5818
www.classiqcoatings.com
technical@classiqcoatings.com

TECHNICAL DATA SHEET

UV FISH CARTON DULL MATT VARNISH UVRM63

DESCRIPTION

UV FISH CARTON SATIN VARNISH UVRM63 is a matt UV overprint varnish for paper and board designed to provide a low odour and dull finish for food & label packaging. UVRM63 has been specially formulated without BENZOPHENONE or 4-METHYL BENZOPHENONE and is ITX free. UVRM63 is suitable for roller coating and flexo application in-line on wet UV inks or off-line on dry conventional inks.

FEATURES

- Matt finish
- Low odour
- High scuff and abrasion resistance
- Good adhesion to a variety of substrates
- Good sealing properties
- Excellent slip
- Low foaming

PROPERTIES

- | | |
|---------------------------|----------------------------------|
| ▪ Cure Speed (80W) | 55 – 65 m/min |
| ▪ Relative Density @ 25°C | 1.17 |
| ▪ Viscosity | 13 – 15 Sec Zahn Cup No.4 @ 25°C |
| ▪ Solids Content | 100% |
| ▪ Recommended Film Weight | 3 – 5 g/m ² |
| ▪ Gloss @ 60° | 10 – 15% |
| ▪ Flashpoint | N/A |

DRYING

By means of UV curing unit.

PACKAGING AND STORAGE

Packed in 25 Kg pails or 200 Kg drums. Storage stability is six months in original, unopened containers at 20°C.

GENERAL

UVRM63 does not contain BENZOPHENONE or 4-METHYL BENZOPHENONE, ITX (Isopropylthioxanthone) or TAA (Titanium Acetylacetonate).

The raw materials used in UVRM63 are acceptable for use under EU regulations governing hazardous materials for the packaging industry. The components used in UVRM63 are not toxic and would be compliant with FDA regulations for indirect food contact.

THIS DATA SUPERCEDES ANY PREVIOUS DATA PRIOR TO APRIL, 2020

